

**IDRATEX UV NO TACK AL C.**

Version 1

Print Date 4/21/2004

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING****Product information**

Product name : IDRATEX UV NO TACK AL C.  
 Product code : MVA8H408000  
 Company : Lechler S.p.A.  
 Via Cecilio 17  
 22100 Rebbio  
 Telephone : +39031586111  
 Telefax : +39031586206

In order to get more information and in case of emergencies please address to Lechler Group Security Office. (Tel. +39-031-586.301).

: Tel. +39-031-586301  
 Fax +39-031-586299

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

**Chemical nature** : Sublimated base

**Hazardous components** :

Components	CAS-No.	EEC-No.	Symbol(s):	R-phrased(s)	Concentration [%]
Methanol	67-56-1	603-001-00-X	T, F	R11, R39/23/24/ 25, R23/24/25	>= 0,1 - < 0,2
2-Idrossi-2-Metilpropiofenone	7473-98-5		Xn, N	R22, R50/53	>= 1 - < 3
Polietere-acrilato insaturo, ammino-sostituito			N	R51/53	>= 20 - < 30
Miscela di alcoli grassi lineari, etossilati			Xn	R22, R36/38	>= 1 - < 3
Naphtha Hydrotreated Heavy	64742-48-9	649-327-00-6	Xn	R65	>= 7 - < 10

**3. HAZARDS IDENTIFICATION**

Dangerous for the environment

**R-phrase(s) :**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**S-phrase(s) :**

Use appropriate containment to avoid environmental contamination.  
Avoid release to the environment. Refer to special instructions/Safety data sheets.

**4. FIRST AID MEASURES**

- General advice : When symptoms persist or in all cases of doubt seek medical advice.  
Never give anything by mouth to an unconscious person.
- After Inhalation : Remove to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious place in recovery position and seek medical advice.
- After Skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Do NOT use solvents or thinners.  
Put shower on working place
- After Eye contact : Irrigate copiously with clean, fresh water for at least 10 minutes,  
holding the eyelids apart.  
Remove contact lenses.  
Seek medical advice.  
Put eye-washer on working place
- After Ingestion : If accidentally swallowed obtain immediate medical attention.  
Keep at rest.  
Do not induce vomiting.

**5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Keep containers and surroundings cool with water spray.
- Extinguishing media which must not be used for safety reasons : Do NOT use water jet.
- Specific hazards during fire fighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10)  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self contained breathing apparatus for fire fighting if necessary.

**6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions : Use personal protective equipment.  
Ventilate the area.  
Refer to protective measures listed in sections 7 and 8.  
Material can create slippery conditions.
- Environmental precautions : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.
- Methods for cleaning up : Clean with detergents. Avoid solvents.  
Contain and collect spillage with non-combustible absorbent material,  
(e.g. sand, earth, diatomaceous earth, vermiculite) and place in  
container for disposal according to local / national regulations (see  
section 13).
- Additional advice : Refer to section 15 for specific national regulation.

**7. HANDLING AND STORAGE**

**Handling**

- Safe handling advice : Avoid exceeding of the given occupational exposure limits (see  
section 8).  
Use only in area provided with appropriate exhaust ventilation.  
Avoid contact with skin, eyes and clothing.  
Smoking, eating and drinking should be prohibited in the application  
area.  
Avoid inhalation of vapour or mist.  
For personal protection see section 8.  
Thoroughly mix before using  
After using, store in a well-sealed container

**Storage**

- Requirements for storage areas and containers : Observe label precautions.  
Containers which are opened must be carefully resealed and kept  
upright to prevent leakage.  
Store in accordance with the particular national regulations.  
Store between 5° and 35°C in a dry, well ventilated place away from  
source of heat, ignition and direct sunlight.  
No smoking.  
Electrical installations / working materials must comply with the  
technological safety standards.
- Advice on common storage : Keep away from oxidising agents and strongly acid or alkaline  
materials.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Components with workplace control parameters**

Components	CAS-No.	Value [mg/m <sup>3</sup> ]	Value [ppm]	Basis
Naphtha Hydrotreated Heavy	64742-48-9	1,755	300,00	

**Personal protective equipment**

- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.  
If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.
- Hand protection : For prolonged or repeated contact use protective gloves.  
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.  
Skin should be washed after contact.  
Wash your hands and put on barrier creams
- Eye protection : Chemical resistant goggles must be worn.
- Skin and body protection : Skin should be washed after contact.  
Personnel should wear protective clothing

**9. PHYSICAL AND CHEMICAL PROPERTIES**

- Form : liquid
- Flash point : > 63 - 100 °C
- Density (specific weight) : 1,07 g/cm<sup>3</sup>
- Viscosity : > 60 s  
Transversale section: 6 mm  
Method: 2431 '84 (ISO 6)
- Solids by weight : 45 %

**10. STABILITY AND REACTIVITY**

- Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions.  
Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.
- Hazardous reactions : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**11. TOXICOLOGICAL INFORMATION**

Acute inhalation toxicity : Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.  
Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.  
Inhalation of airborne droplets may cause irritation of the respiratory tract.

Skin irritation : Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin.  
The product may be absorbed through the skin.

Note : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

Methanol  
OBSERVATIONS ON HUMAN SUBJECTS: Methanol poisoning as a result of ingestion produces three types of effect. The first to appear is a narcotic effect, similar to that observed in ethanol poisoning. The next to appear is metabolic acidosis, caused by an accumulation of formate which is produced more quickly than it is eliminated. The third type of effect consists in disorders affecting vision and the nervous system. In human subjects, exposure (of variable intensity and duration) to methanol vapours causes irritation to all the mucous membranes, headache, buzzing in the ears, tiredness, insomnia, nystagmus, tremors, dizziness, nausea, colic, dilated pupils, double vision, blindness, itching of the skin, eczema and dermatitis.

**12. ECOLOGICAL INFORMATION**

Further information : The product contains dangerous substances for the environment (see chapter n° 2), The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

2-Idrossi-2-  
Metilpropiofenone

R50

Very toxic to aquatic organisms.

### 13. DISPOSAL CONSIDERATIONS

Product : The product should not be allowed to enter drains, water courses or the soil.  
Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

### 14. TRANSPORT INFORMATION

**ADR** : Not classified as dangerous in the meaning of transport regulations.

**IMDG** : Not classified as dangerous in the meaning of transport regulations.

**IATA** : Not classified as dangerous in the meaning of transport regulations.

### 15. REGULATORY INFORMATION

Hazardous components which must be listed on the label:

Symbol(s): : N Dangerous for the environment

R-phrases) : R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases) : S57 Use appropriate containment to avoid environmental contamination.  
S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

#### National legislation

Germany

Risk classification according to German VbF : not applicable

### 16. OTHER INFORMATION

**Further information**

Methanol	R11 R39/23/24/25	Highly flammable. Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
	R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
2-Idrossi-2-Metilpropiofenone	R22 R50/53	Harmful if swallowed. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Polietere-acrilato insaturo, ammino-sostituito	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Miscela di alcoli grassi lineari, etossilati	R22 R36/38	Harmful if swallowed. Irritating to eyes and skin.
Naphtha Hydrotreated Heavy	R65	Harmful: may cause lung damage if swallowed.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Version: 1

Revision date 22.04.2002

SDS updated to the 27th adjustment EEC directive 1999/45/CE.